

ATKOMATIC

15800 Series

Stainless Steel, Semi-direct Lift, Pressure 0 to 1500 psig (104 bar)
Medium Pressure Valve Configurable for Variety of Fluid Applications



atkomatic solenoid

Features

- Stainless steel construction on all wetted parts: 316 for barstock parts and CF8M for cast parts.
- Plunger material is 416 stainless that is treated for increased corrosion resistance
- Semi-direct lift action for operation down to zero pressure differential
- Normally closed operation
- Operation up to 1500 psi (104 bar)
- Media temperatures from -423°F to $+500^{\circ}\text{F}$ (-253°C to $+260^{\circ}\text{C}$)
- Will handle fluids with viscosity up to 150 SUS
- Suitable for use with wide variety of fluid including: air, gasses, liquids, hydraulic fluids, steam, cryogenic fluids, and corrosive fluids
- Optional pilot and piston seat materials of Teflon[®], PCTFE, Buna N, Viton[®], EPR, or 316 stainless steel depending on fluid type and pressure
- Body seal materials of Teflon[®], Viton[®], Buna N, or EPR
- Pipe sizes from $\frac{1}{4}$ " through 1" NPT
- British BSPT ports are available
- Full ported valves: Cv from 1.1 through 12.5
- Removable 316 stainless steel body inserts (stainless steel trim)
- Class H coils standard
- Coil housings available in NEMA 1 (standard), NEMA 4 (waterproof), NEMA 7 (explosion-proof for hazardous locations), and combination NEMA 4 & 7
- Manual opening device is available as an option
- Valve position indicator option is available

Operational Pressures (No minimum pressure differential)

GASES		LIQUIDS TO 40 SUS		LIQUIDS OVER 40 SUS		STEAM	
AC	DC	AC	DC	AC	DC	AC	DC
1500 / 104 bar	1500 / 104 bar	1500 / 104 bar	1000 / 69 bar	1500 / 104 bar	1000 / 69 bar	200 / 14 bar	200 / 14 bar

Note: Buna N, Viton[®] and EPR seats are limited to 500 psi.

Circle Seal Controls

2301 Wardlow Circle • P.O. Box 3300 • Corona, CA 92880

Phone (951) 270-6200 Fax (951) 270-6201

www.circle-seal.com • am_sales@circle-seal.com • ind_sales@circle-seal.com

